

**IN THE CLAIMS:**

---

Please cancel claim 1.

Please amend the claims as follows.

1. (Cancelled)

2. (Currently Amended) A method according to claim 1 12, characterized in that the at least one parameter is determined in some fixed network element of the network, such as a base station system (~~BSS~~) or a support node (~~SGSN~~).

3. (Currently Amended) A method according to claim 1 12, characterized in that the at least one parameter is determined in the terminal equipment (~~MS, PC~~).

4. (Currently Amended) A method according to claim 2, characterized in that the at least one parameter is determined on the basis of the utilization ratio of the capacity of the base station system (~~BSS~~).

5. (Currently Amended) A method according to claim 2, characterized in that the at least one parameter is determined on the basis of time stamps of the downlink packets.

6. (Currently Amended) A method according to claim 2, characterized in that the at least one parameter is determined by the success probability of resource reservation attempts or on the basis of the waiting times of resource reservations.

7. (Currently Amended) A method according to claim 2, characterized in that the at least one parameter is sent to the terminal equipment (~~MS, PC~~) on a broadcast channel, preferably on BCCH or PBCCH.

8. (Currently Amended) A method according to claim 2, characterized in that the at least one parameter is sent to the terminal equipment (~~MS, PC~~) as a Point-To-Multipoint transmission.

9. (Currently Amended) A method according to claim 2, characterized in that the at least one parameter is sent at least to some terminal equipments (~~MS, PC~~), preferably to a terminal equipment that has just registered to the network, individually, such as a Point-To-Point transmission or a short message.

10. (Currently Amended) A method according to claim 2, characterized in that the at least one parameter is determined in more than one class for the quality of service.

11. (Currently Amended) A method according to claim 2, characterized in that the at least one parameter is determined in all classes for the quality of service in the packet radio network.

12. (Currently Amended) A method ~~according to claim 1,~~ for indicating a prevailing overall service situation in a packet radio network which includes at least one base station and at least one terminal equipment and where several classes for the quality of service have been determined;

characterized by

determining at least one parameter representing the overall service situation of the packet radio network; and

supplying the at least one parameter to the use of the terminal equipment,  
~~characterized in that~~ wherein the at least one parameter is determined relating to at least two base station systems (BSS) and the at least one parameter is employed as a crossover criterion.

13. (Currently Amended) A method according to claim 4 ~~12~~, characterized in that the at least one parameter is made available to the application program being executed in the terminal equipment (MS, PC).

14. (Currently Amended) A method according to claim + 12, characterized in that the at least one parameter is made available to the application program being executed in the terminal equipment (~~MS, PC~~).

*31*  
*Con'd.* 15. (Currently Amended) A method according to claim 14, characterized in that at least one nominal value is defined for said application program and the application program independently negotiates a new class for the quality of service if said at least one parameter deviates essentially from said nominal value.

---